



SmartTrack 100 Series Meters and Controllers: 100, 101, and 140

Take it on the water with the most advanced in the world in a compact, rugged, and easy-to-use package.

FEATURES

- 1. Real-time and historical logging (up to 1000 hours) with 100% of the unit's battery capacity reserved for logging.
- 2. **SmartTrack 100 Series** (100, 101, 140) is the only one in the world with integrated GPS, allowing you to track, mark, and measure. SmartTrack 100 Series meters and controllers are available in 12V and 24V versions. SmartTrack 140 is a 24V only meter and controller. (Maximum performance is reserved.)

INSTALLATION

- 1. Complete the basic installation using a standard 1/2" diameter 3/16" spacing standard (1/2" diameter or 3/4" diameter) or a 1/2" diameter 1/4" spacing standard (1/2" diameter or 3/4" diameter) standard (1/2" diameter or 3/4" diameter).
- 2. Mount the meter and controller on a flat surface. The unit is designed to be mounted on a standard 1/2" diameter 1/4" spacing standard (1/2" diameter or 3/4" diameter) standard (1/2" diameter or 3/4" diameter).
- 3. The meter and controller are designed to be mounted on a standard 1/2" diameter 1/4" spacing standard (1/2" diameter or 3/4" diameter) standard (1/2" diameter or 3/4" diameter).
- 4. **SmartTrack 100 Series** is the only meter and controller in the world with a standard 1/2" diameter 1/4" spacing standard (1/2" diameter or 3/4" diameter) standard (1/2" diameter or 3/4" diameter).
- 5. The meter and controller are designed to be mounted on a standard 1/2" diameter 1/4" spacing standard (1/2" diameter or 3/4" diameter) standard (1/2" diameter or 3/4" diameter).
- 6. The meter and controller are designed to be mounted on a standard 1/2" diameter 1/4" spacing standard (1/2" diameter or 3/4" diameter) standard (1/2" diameter or 3/4" diameter).