

## SmartTrak® 50 Series Low & Medium Flow Quick Install Guide

### INTRODUCTION

Congratulations on your purchase of the SmartTrak® 50 Series digital gas mass flow rate controller designed to meet the low cost budgetary requirements of OEM's while maintaining excellent quality and performance. This reference guide is put here to replace the Instruction Manual included on the CD-ROM in your shipment, but rather is a great supplement to it that will help you install and operate your instrument and begin to measure or control mass flow.

### SAFETY 1<sup>st</sup>

1. Apply power only after reviewing the wiring diagrams through 2 of this guide or in the Instruction Manual.
2. Apply gas flow only after checking/validating connections for leaks.
3. **NEVER TEST FOR GASES WITH GASES (GAS DETECTION).** If liquid seeps into the electronics or the hidden sensor compartment, the instrument may be damaged! Instead use vapors or a dry test (if liquid MUST be used at all, test it to the fumes and keep it off the body of the instrument).

### INSTALLATION

1. Consult the instrument's Data Label (on the back of the instrument) for its proper operating parameters. If the information on the Data Label does not match your process conditions, contact your Representative or Sierra Instruments Customer Service at the contact information on the back of the sheet.
2. Install a 30 micron or finer filter upstream of your instrument. If the gas contains any moisture, use an appropriate dryer or desiccant. Particles larger than 10 microns and moisture may damage your instrument.
3. Mount according to Data Label orientation. Horizontal flow is preferable and factory default unless the factory calibration was performed specifically for vertical flow upward or downward, as listed. Orientation is listed on Data Label and on the Calibration Certificate.
4. This instrument is not a plug-powered device! Do NOT apply power to the 4-20 mA, 0-5 VDC output or output connections.
5. Wire your instrument per the Diagrammed pin out on the back of this card and in Chapter 2 of the Instruction Manual. For convenience of wiring, there are two DB9 connector ports, the second DB9 is capped off. Apply power to your choice of port and cap second port. It is recommended you allow 30 minutes for the instrument to warm up for maximum accuracy.

### OPERATION

1. Power the unit. If you are using the Sierra provided power supply, it is recommended you attach the 3-wire connector to the 50 Series before plugging the adapter into the wall. The unit may take longer to start than normal if otherwise. This will not damage the unit in any way.
2. Our Mass Flow Controllers with a digital output option are shipped with a zero output in the power up output point in the software. For safety considerations, it is recommended 100% confirm this prior to applying gas to the unit.
3. Apply the gas listed on the Data Label to the inlet at the recommended pressure (listed on the Data Label) Calibration Certificate). Your 50 Series will begin to measure mass flow. This will be displayed on the user software or local display.
4. You will need a output input in order to control flow. **Be exceptionally** You can digitally input a output using the user software or control directly with your analog output source if you ordered the analog option. **NOTE:** The unit ships in

#### WARRANTY: We are here to help when you need it!

Need Tech Support? [sierra@sierrainstruments.com](mailto:sierra@sierrainstruments.com)

24 Hour Website Service: [www.sierrainstruments.com](http://www.sierrainstruments.com) 24/7 "Yes & Service" button

Tech Support & America: 800-884-2222 or 800-274-2222 Europe: 01-753274 440-884-2222 or 440-274-2222