

"HA" Mini Pressure Transmitters

Features

The HA series offers the most compact and rugged pressure transmitters available for industrial applications. The HA series consists of two models: HA-1 and HA-2. The HA-1 is designed for applications requiring a wide range of pressure ranges and output options. The HA-2 is designed for applications requiring a wide range of pressure ranges and output options. The HA series is designed for applications requiring a wide range of pressure ranges and output options. The HA series is designed for applications requiring a wide range of pressure ranges and output options.



Specifications

Feature	HA-1	HA-2	HA-1/2
Pressure Range	0 to 1000 psig (0 to 70 bar)	0 to 1000 psig (0 to 70 bar)	0 to 1000 psig (0 to 70 bar)
Accuracy	±0.1% FS	±0.1% FS	±0.1% FS
Output	4-20 mA	0-5 VDC	0-5 VDC
Supply Voltage	12-30 VDC	12-30 VDC	12-30 VDC
Operating Temperature	-40 to 125 °C	-40 to 125 °C	-40 to 125 °C
Storage Temperature	-40 to 125 °C	-40 to 125 °C	-40 to 125 °C
Material	316L SS	316L SS	316L SS
Process Connection	1/4" NPT	1/4" NPT	1/4" NPT
Electrical Connection	3-pin	3-pin	3-pin
Weight	0.15 lb	0.15 lb	0.15 lb
Dimensions	1.5" x 1.5" x 1.5"	1.5" x 1.5" x 1.5"	1.5" x 1.5" x 1.5"
IP Rating	IP67	IP67	IP67
Mounting	Panel Mount	Panel Mount	Panel Mount
Lead Time	1 week	1 week	1 week