

# Potentiometric Level Sensor NSL-F

## Application Features

- Suitable for measuring level in water, acids and alkalis
- Made of stainless steel, suitable for aggressive media
- Temperature range: 0...120 °C
- Operating voltage: 12V DC, 24V DC or 48V DC
- Suitable for measuring level in: **water**
- **Aggressive media** like: **acids**

## Application Areas

- Sewage water level measurement
- Industrial water level measurement
- Environmental protection work

## Application Advantages

- High accuracy, precision and stability
- Long-term, trouble-free operation and maintenance-free
- All stainless steel, 316L version
- Easy installation, easy to maintain
- High accuracy, stable measurement
- The stainless steel 316L version is suitable for aggressive media
- High accuracy, precision and stability

## Special Features

- High accuracy, precision and stability
- Long-term, trouble-free operation and maintenance-free
- All stainless steel, 316L version
- Easy installation, easy to maintain
- High accuracy, stable measurement
- The stainless steel 316L version is suitable for aggressive media
- High accuracy, precision and stability
- High accuracy, precision and stability
- High accuracy, precision and stability
- High accuracy, precision and stability

## Technical Data

- Operating voltage: 12V DC, 24V DC or 48V DC
- Operating temperature: 0...120 °C
- Accuracy: ±0.1 mm
- Response time: 100 ms

## Accessories

- **NSL-F-12V**
- **NSL-F-24V**

## Technical Data

- **Operating voltage:** 12V DC, 24V DC or 48V DC
- **Operating temperature:** 0...120 °C
- **Accuracy:** ±0.1 mm
- **Response time:** 100 ms

## Technical Drawing (1)



## Technical Drawing (2)

