



DIFFERENTIAL PRESSURE TRANSMITTERS

"All Stainless Steel"

Series DP-4000



▶ STAINLESS STEEL HOUSING

▶ EASY ADJUSTABLE WITHOUT

TOOLING (UP TO 1 BAR/100)

▶ ACCURACY $\pm 0.075\%$

OFFLINE $\pm 0.065\%$

▶ ZERO ADJUST UP TO 100:1

▶ GRAPHIC DISPLAY WITH

BACKGROUND AND BATTERY

▶ HART PROTOCOL (HART 1)

▶ DEVELOPMENT ACCORDING TO SIL2

▶ BATTERY LIFE IS AVAILABLE



HART



Description

The DP-4000 is a high performance differential pressure transmitter with a compact and robust **Stainless steel electronics housing**. The calibration / programming can be done very easy without instruments by using the **Onsite tool programming** (on-site tool) together with the **Graphic display with backlight**. The multicolor graphic display can indicate a number of chosen engineering units including the process temperature as well as the set-point (in barg). Sampling time can be adjusted with a 4-20 mA current simulation can be performed. For flow measurement a square root function is built-in with adjustable cut-off point. The output is 4-20 mA including HART protocol (HART 1) or HART 2. IFC, IFC-2, IFC-3, IFC-4, IFC-5 and IFC-6 approvals are available.



Address:

KLAY-INSTRUMENTS B.V.

Address:

Postbox 2
7400 AA De Bilt
T: +31 (0) 30 600 000
E: info@klay.nl

Web site:

www.klay.nl