




'INTELLIGENT' PRESSURE- AND LEVEL TRANSMITTERS

For all industries

Series 2000




- "ALL STAINLESS" DESIGN
- HART CALIBRATION WITHOUT TEST PRESSURE BY 3 PUSH BUTTONS
- ACCURACY 0.1%
- 4-20 mA AND HART PROTOCOL
- ATEN  0.1 Class 1.0
- WIDE RANGEABILITY
- LOCAL DISPLAY
- ADJUSTABLE DAMPING
- WIDE TANK AND PIPELINE PROCESS CONNECTIONS
- OPTION HART PROTOCOL

HART 
COMMUNICATIONS PROTOCOL

Description

The Series 2000 is a complete range of intelligent pressure and level transmitters with local display and adjustment by three pushbuttons. The pushbuttons are suitable for zero and span. Test pressures are not required for calibration.

The display which can indicate a number of chosen engineering units is also used during programming to assist the easy operation. Process temperature can be shown and damping times can be selected from 0 to 25 secs. Also a 4-20 mA Current Simulation can be performed.

The Series 2000 is fully temperature compensated. Over 40 different process connections are available including many flush diaphragm designs. Options include ATEN  approval or HART protocol.

HART is a registered trademark of the HART Communications Foundation.



 **KLAY-INS RUMENTS B.V.**

 **SMEI**